

AGV King Off-Grid Inverter



- Zero transfer time to protect mission-critical loads such as servers and ATM.
- Detachable LCD control module with multiple communications
- Built-in Bluetooth for mobile monitoring (Android App is available)
- Supports USB On-the-Go function
- Reserved communication port for BMS (RS485, CAN-BUS or RS232)
- Configurable AC/PV output usage timer and prioritization
- Optional parallel operation up to 9 units

AGV King Off-Grid Inverter Selection Guide

MODEL	AGV King 3K	AGV King 5K
Rated Power	3000VA/3000W	5000VA/5000W
Parallel Capability	Up to 9 units	Up to 9 units
INPUT		
Voltage	230 VAC	
Voltage Range	110-280 VAC	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation	230 VAC ± 5%	
Output THDv	<3% for linear load, <8% for non-linear load	
Surge Power	6000VA for 5 sec	10000VA for 5 sec
Efficiency (Peak)	93 % at Line Mode, 90% at Battery Mode	
Transfer Time	0 ms	
Waveform	Pure sine wave	
BATTERY		
Battery Voltage	24 VDC	48 VDC
Floating Charge Voltage	27 VDC	54 VDC
Overcharge Protection	34 VDC	66 VDC
SOLAR CHARGER & AC CHARGER		
Solar Charger Type	MPPT	MPPT
Maximum PV Array Open Circuit Voltage	145 VDC	
Maximum PV Array Power	1500 W	4000 W
MPP Range @ Operating Voltage	30 ~ 115 VDC	60~115VDC
Maximum Solar Charge Current	60 A	80 A
Maximum AC Charge Current	60 A	60 A
Maximum Charge Current	120 A	140 A
PHYSICAL		
Dimension, D x W x H (mm)	140 x 303 x 525	
Net Weight (kgs)	13.0	13.5
Communication Interface	USB/RS232/RS485/Bluetooth/Dry-contact	
ENVIRONMENT		
Humidity	5% to 95% Relative Humidity (Non-condensing)	
Operating Temperature	0°C to 55°C	
Storage Temperature	-15°C to 60°C	

Abdulmajeed AL-Wahbani Trading Group (ATG)
 Yemen Sana'a Hada St. Near to AL-Gharasi building
 TEL: +967 1 211764 MOBILE: +967 777222725



مجموعة عبدالمجيد الوهباني للتجارة
 اليمن - صنعاء - حدة جوار عمارة الفراسي
 تليفاكس / ٢١١٧٦٤ جوال ٧٧٧٢٢٢٧٢٥



For sales, service and other enquiries,
 email us info@atg-ye.com

www.atg-ye.com

للمبيعات، الخدمات والطلبات الأخرى
 راسلنا على info@atg-ye.com

